

Email: legionspeedway@gmail.com

Website: legionspeedwaynh.com

Track phone: 603 - 764-6060

Sportsman Modified

*2022

*2022 These rules are originally the 2021 RumTown Speedway rules and are subject to change as Legion Speedway takes over the track and learns more about each division.

Bodies:

- 1. Any coupe or modified type with roof, no age limit
- 2. All cars must have drive shaft tunnel with steel safety loop
- 3. Added weight must be painted white with your cr number on it
- Added weight must be mounted to the roll cage by a minimum of two half inch grade 8 bolts
- 5. Wing and sail panels are allowed.. This rule may change in 2022

Shocks:

- 1. 2 ½" diameter coil springs allowed
- 2. Coil overs allowed
- 3. Leaf springs allowed
- 4. Tie rod and steering arms may use heim joints
- 5. 4 shocks maximum price \$200.00 per shock. No on board adjustable shocks. No remote reservoir or dual adjustable shocks allowed. The price per shock is based on the manufacturer's retail price.

Drive Train:

- 1. Any transmission allowed. Must have steel bell housing, or steel scatter shield
- 2. Any clutch
- 3. Any rear end allowed
- 4. Steel or aluminum drive shaft only. Must be painted white
- 5. Reverse gear must work
- 6. All cars must be self starting

Engine Rule #1:

602 GM Performance **SEALED** Crate engine. This engine must be run as manufactured including a stock GM harmonic balancer. Exception: Aluminum water pump is allowed.

- Factory seal bolts with GM barcode and logo must remain intact. If your motor
 has been opened up or rebuilt it is subject to a whistle test for compression and a
 bubble test for cubic inch.
- All modified must run a rev limiter with a maximum 6200 chip. Must be a
 DIGITAL limiter. Rev box must be mounted in engine compartment, out of the
 reach of the driver

Holley 650 cfm series 4150 with 1 inch max spacer, must pass GO NO GO GAUGE

Stock HEI Distributor, must be black cap with white rotor. No alterations

Engine Rules # 2:

- 1. Home Built small block Chevrolet
- 2. No aluminum blocks
- 3. Stock 4412 Holley 500 2bbl. Must pass GO NO GO GAUGE
- 4. Maximum 1 inch spacer
- 5. GM HEI ignition, may be locked down, must be black cap with white rotor
- 6. Must run a rev limiter with a maximum 6200 chip. Must be a **DIGITAL** limiter. Rev box must be mounted in engine compartment, out of the reach of the driver

Exhaust:

- 1. No Tri-Y step headers, stainless steel coated or ceramic and merge collectors will not be permitted
- 2. Mufflers are required

Roll Cage:

- 1. 1 ½" .090 wall full cage is mandatory
- 2. Floor and sides around the driver must be 1/8" steel plate
- 3. Approved racing aluminum seat only. Mounted with 6 %" grade 8 bolts
- 4. Approved seat belts must be SFI rated. No more than 3 years old
- 5. Fire extinguisher is recommended
- 6. Mandatory fuel cell must be securely mounted in the trunk area

Wheels and Tires:

- 1. Right rear, any brand 29 or 92 as labeled by manufacturer. Tires may be up to 14" wide.
- 2. 14 inch tread width, BRS Hoosier DIRT soft or hard allowed
- 3. Bead locks allowed
- 4. 1inch lug nuts mandatory
- 5. All cars must have working brakes on all four wheels

Weight:

All cars must have a total minimum weight with a driver of 2350 lbs. Weight is after the race. No allowance for racing laps.

Interpretation of the rules by an official is FINAL. The management reserves the right to change any rule or rules if they feel it is necessary. Any refusal to having your car inspected will result in points and money forfeited for the night or not being able to compete. If you are found to be illegal you will forfeit any money or points for the event. You will be required to start at the back of the lineup for the next three events you compete in.

It would be impossible to cover all the aspects of everything allowed or disallowed. Just because it is not covered in the rules does not mean it is OK. Check with the rules official first. Do not **ASSUME** you can do something just because it is not stated in the rules.